

Wireless sensors



Blue PUCK RHT

Ref. IDF25242



The new industry standard in the wireless Temperature & Humidity sensor's market!

- 👁️ Very long range: up to **500 meters** (open field)
- 👁️ High lifecycle: up to **13 years**
- 👁️ Robust industrial casing - **IP65 waterproof**
- 👁️ Integrated **NFC** chipset

<i>Technical specifications</i>	
Battery power supply	3 VDC - Lithium internal battery
Frequency	2,4 GHz - Bluetooth Low Energy 4.0/4.2
Operating mode	"Advertising" beacon mode: periodic data transmission (id + measures) Connected mode: download up to 2,000 stored Temperature & Humidity values
Power output	Up to +4dBm (programmable)
Transmission range	Up to 500 meters (open field / + 4dBm)
Transmission period	0,1 to 10 second (programmable)
Lifecycle	13 years (Beacon rate = 10s with +4dBm)
Radio frame format	ID: 15 characters name Unique 48 bits MAC address 👁️ Temperature: 16 bits 👁️ Humidity: 8 bits ID (ELA) compliant
Setting & configuration	Interface/Protocol: NFC Type 2 Device Manager software or Device Manager Mobile Android App
Sensor: Measuring range	Temperature: -40°C to 85°C / Humidity: 0 to 100%
Sensor: Resolution	Temperature: 0.015°C / Humidity: 0.01%
Sensor: Accuracy	Temperature: ±0.3°C TYP from -40°C to 85°C
Operating temperature	-30°C à +85°C
Battery level management	Send battery level from 15%
Housing	∅ 57mm base - Thickness 18mm 2 mounting ∅ 4mm holes, spaced of 49mm IP65 Waterproof - Weight 36g DELRIN (POM C) material – Food Grade (90/128/EEC)
Standards	EC (Europe)*: EN 300 328/ EN 301 489 & EN 55032 / EN 62368-1 FCC (USA)*: FCC 15.247 / FCC PT 15B ISED/IC (Canada)*: RSS-247 / ICES-003 RoHS certified (*) Certification in progress
Accessories	PUCK HOLDER STICKER (ACIOM118)